

Grade : F & P Series

Product Name: Polyethylene Wax
General Purpose: Internal & External Lubricant
Appearance : White Flake and Powder Grades
Application: Use as additives for hotmelt adhesive ,Powder Coating ,PVC, Masterbatch, Emulsion, Architecture Papers, Stabilizer & Etc.
Packing: 20kg bag on plastic pallet
Storage: Dry Storage under 30°C is recommended.

PE WAX – Turkey Plant

Properties	Unit	Test Method	F152T	F175	F160	F165	P190
Melting Point	°C	ASTM D 3954	90~110	95~110	105~115	105~115	105~115
Viscosity @140°C	Cp	ASTM D 3236	Max 50	Max 60	Max 25	Max 30	Max 25
Density	gms/cc	ASTM D 1505	0.90~0.9 2	0.90~0.9 2	0.90~0.92	0.90~0.92	0.90~0.9 2
Penetration	0.1mm	ASTM D 1321	10~20	3~9	2~5	1~2	1~1.5

PE WAX – South Korea Plant

Properties	Unit	Test Method	F175K	P195K
Melting Point	°C	ASTM D 3954	90~105	95~110
Viscosity @140°C	cp	ASTM D 3236	Max 50	Max 50
Density	gms/cc	ASTM D 1505	0.90~0.92	0.90~0.92